



## K25L18 AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	497 L/MIN ~ 17.6 CFM
FREE AIR DELIVERY (to AS4637)	365 L/MIN ~ 12.9 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	3.0 KW ~ 4.0 HP 415 V 50HZ <b>NOTE: NOT SUPPLIED WITH LEAD &amp; PLUG</b>
REQUIRED CIRCUIT BREAKER	16 AMP **
RECEIVER	100 LITRE (STATIC), TO AS1210
DIMENSIONS	1060mm L X 450mm W X 900mm H
WEIGHT	130 KG*
AIR OUTLET	1/4" BSP

\* APPROX ONLY  
\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

[www.pilotair.com.au](http://www.pilotair.com.au)  
[enquiries@airandpower.com.au](mailto:enquiries@airandpower.com.au)