

K17SI AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637) FREE AIR DELIVERY (to AS4637) MAXIMUM CUT OUT PRESSURE COMPRESSOR PUMP MOTOR

NOISE LEVEL REQUIRED CIRCUIT BREAKER RECEIVER DIMENSIONS WEIGHT AIR OUTLET 428 L/MIN ~ 15.1 CFM 292.6 L/MIN ~ 10.3 CFM 1000 KPA ~ 145 PSI TWIN CYLINDER, SINGLE STAGE, ITALIAN MADE 2.2 KW ~ 3.0 HP 415 V THREE PHASE 50HZ **NOTE: NOT SUPPLIED WITH PLUG** 63 d(B)a 10AMP ** NOT SUPPLIED A SEPERATE 100 LITRE RECEIVER IS RECOMMENDED 730mm L X 640mm W X 1100mm H 147 KG* 1/4" BSP (1 x regulated & 1 x non-regulated) * APPROX ONLY

** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- ITALIAN DESIGNED AND BUILT
- INBUILT PRESSURE REGULATOR
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 1 YEAR ON ALL COMPONENENTS