

## K30P AIR COMPRESSOR – PETROL DRIVEN

PISTON DISPLACEMENT (to AS4637)	981 L/MIN ~ 34.7 CFM
FREE AIR DELIVERY (to AS4637)	812.2 L/MIN ~ 28.7 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
ENGINE	HONDA GX390 ELECTRIC START <b>NOTE: BATTERY &amp; LEADS NOT INCLUDED</b>
RECEIVER	200 LITRE (STATIC PALLET FEET), TO AS1210
DIMENSIONS	1410mm L X 500mm W X 1050mm H
WEIGHT	220 KG*
AIR OUTLET	3/4" BSP

\* APPROX ONLY



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- PNEUMATICALLY CONTROLLED AUTOMATIC IDLE DOWN CONTROL
- “EASY START VALVE”
- WARRANTY: 3 YEARS ON PUMP, 2 YEARS ON THE MOTOR, 1 YEAR ON ALL OTHER COMPONENTS