

K50L AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637) 1120 L/MIN \sim 39.6 CFM FREE AIR DELIVERY (to AS4637) 888 L/MIN \sim 31.3 CFM MAXIMUM CUT OUT PRESSURE 1100 KPA \sim 160 PSI

COMPRESSOR PUMP TWIN CYLINDER, TWO STAGE, ITALIAN MADE

MOTOR 7.5 KW ~ 10.0 HP 415 V THREE PHASE 50HZ

NOTE: NOT SUPPLIED WITH LEAD & PLUG

REQUIRED CIRCUIT BREAKER 32 AMP **

RECEIVER 600 LITRE (STATIC), TO AS1210, AUSTRALIAN MADE
DIMENSIONS 2100mm L X 740mm W X 1340mm H
WEIGHT 250 KG*
AIR OUTLET 3/4" BSP

* APPROX ONLY
** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS