

K100 AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	2,311.4 L/MIN ~ 81.6 CFM
FREE AIR DELIVERY (to AS4637)	1,913 L/MIN ~ 67.6 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	FOUR CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	15 KW ~ 20 HP 415V THREE PHASE 50HZ COMPLETE WITH STAR DELTA STARTER NOTE: NOT SUPPLIED WITH LEAD & PLUG
REQUIRED CIRCUIT BREAKER	50 AMP **
RECEIVER	500 LITRE (STATIC), TO AS1210
DIMENSIONS	1890mm L X 700mm W X 1560mm H
WEIGHT	480 KG*
AIR OUTLET	3/4" BSP

* APPROX ONLY
** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS