

## K25/21-V AIR COMPRESSOR- 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	581 L/MIN ~ 20.5 CFM
FREE AIR DELIVERY (to AS4637)	454 L/MIN ~ 16 CFM
MAXIMUM CUT OUT PRESSURE	1100 KPA ~ 160 PSI
COMPRESSOR PUMP	TWIN CYLINDER, TWO STAGE, ITALIAN MADE
MOTOR	4.0 KW ~ 5.5 HP 415V THREE PHASE 50HZ <b>NOTE: NOT SUPPLIED WITH LEAD &amp; PLUG</b>
REQUIRED CIRCUIT BREAKER	20 AMP **
RECEIVER	150 LITRE (STATIC, VERTICAL), TO AS1210, AUSTRALIAN MADE
DIMENSIONS	780mm L X 620mm W X 1980mm H
WEIGHT	160 KG*
AIR OUTLET	3/4" BSP

\* APPROX ONLY

\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- COMPACT FOOTPRINT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS