

## K30-V AIR COMPRESSOR – 415V THREE PHASE

|                                 |   |
|---------------------------------|---|
| PISTON DISPLACEMENT (to AS4637) | 871.8 L/MIN ~ 30.8 CFM  |
| FREE AIR DELIVERY (to AS4637)   | 681 L/MIN ~ 24.1 CFM  |
| MAXIMUM CUT OUT PRESSURE        | 1100 KPA ~ 160 PSI  |
| COMPRESSOR PUMP                 | TWIN CYLINDER, TWO STAGE, ITALIAN MADE  |
| MOTOR                           | 5.5 KW ~ 7.5 HP 415V THREE PHASE 50HZ<br><b>NOTE: NOT SUPPLIED WITH LEAD &amp; PLUG</b> |
| REQUIRED CIRCUIT BREAKER        | 25 AMP **   |
| RECEIVER                        | 150 LITRE (STATIC, VERTICAL), TO AS1210, AUSTRALIAN MADE                                |
| DIMENSIONS                      | 780mm L X 620mm W X 2050mm H  |
| WEIGHT                          | 190 KG*   |
| AIR OUTLET                      | 3/4" BSP  |

\* APPROX ONLY

\*\* INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



### FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- COMPACT FOOTPRINT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS