



K30SI AIR COMPRESSOR – 415V THREE PHASE

| | |
|---------------------------------|---|
| PISTON DISPLACEMENT (to AS4637) | 871.8 L/MIN ~ 30.8 CFM |
| FREE AIR DELIVERY (to AS4637) | 681 L/MIN ~ 24.1 CFM |
| MAXIMUM CUT OUT PRESSURE | 1100 KPA ~ 160 PSI |
| COMPRESSOR PUMP | TWIN CYLINDER, TWO STAGE, ITALIAN MADE |
| MOTOR | 5.5 KW ~ 7.5 HP 415 V THREE PHASE 50HZ NOTE: NOT SUPPLIED WITH PLUG |
| NOISE LEVEL | 66 d(B)a |
| REQUIRED CIRCUIT BREAKER | 25 AMP ** |
| RECEIVER | NOT SUPPLIED. A SEPARATE 147 LITRE RECEIVER IS RECOMMENDED |
| DIMENSIONS | 900mm L X 640mm W X 1100mm H |
| WEIGHT | 182 KG* |
| AIR OUTLET | 3/4" BSP |

* APPROX ONLY

** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- ITALIAN DESIGNED AND BUILT
- OVER TEMPERATURE PROTECTION
- THERMOSTATICALLY CONTROLLED COOLING FANS
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 1 YEAR ON ALL COMPONENTS