



## ACT23T REFRIGERATED AIR DRYER

FLOW RATE (L/s / CFM)	38.2 / 81
MAXIMUM PRESSURE (Bar / PSI)	14 / 203
POWER SUPPLY (Volt)	240V
DIMENSIONS (LxWxH mm)	455 x 485 x 785
WEIGHT (KG)	41
PORT SIZE - FEMALE (BSP)	1"



### UNIQUE COOLING SYSTEM

- High efficiency cooling module
- Reduces energy consumption
- Means minimal pressure drops even with load variances
- The pressure dewpoint is constantly maintained

### BUILT FOR AUSTRALIAN CONDITIONS

- Designed with Australian conditions in mind
- Flow rates based on an ambient temperature of 35° Celsius and an inlet temperature of 42° Celsius

### COMPACT

- Compact design saves on valuable floor space

### AUTOMATIC DRAIN

- Fitted with a timed electronic automatic condensate drain
- Discharge and pause times are adjustable

### WARRANTY

- One year warranty
- Please note that a 5 micron prefilter is required on the inlet side of the dryer to prevent rust or scale clogging the dryer

[www.pilotair.com.au](http://www.pilotair.com.au)  
[enquiries@airandpower.com.au](mailto:enquiries@airandpower.com.au)