



K17T AIR COMPRESSOR – 415V THREE PHASE

PISTON DISPLACEMENT (to AS4637)	428 L/MIN ~ 15.1 CFM
FREE AIR DELIVERY (to AS4637)	292.6 L/MIN ~ 10.3 CFM
MAXIMUM CUT OUT PRESSURE	1000 KPA ~ 145 PSI
COMPRESSOR PUMP	TWIN CYLINDER, SINGLE STAGE, ITALIAN MADE
MOTOR	2.2 KW ~ 3.0 HP 415 V THREE PHASE 50HZ NOTE: NOT SUPPLIED WITH LEAD & PLUG
REQUIRED CIRCUIT BREAKER	10AMP **
RECEIVER	100 LITRE (STATIC), TO AS1210
DIMENSIONS	1060mm L X 400mm W X 860mm H
WEIGHT	100 KG*
AIR OUTLET	1/4" BSP

* APPROX ONLY
** INDICATIVE ONLY, PLEASE CHECK WITH YOUR ELECTRICIAN



FEATURES

- AUSTRALIAN DESIGNED AND BUILT
- INDUSTRIAL GRADE HAMMERTONE ENAMEL FINISH
- CAST IRON CYLINDER PUMP
- ELECTRIC MOTOR OVERLOAD
- WARRANTY: 3 YEARS ON PUMP, 1 YEAR ON ALL OTHER COMPONENTS

www.pilotair.com.au
enquiries@airandpower.com.au